

78



The 78 Series valves are full-port PN40 flanged, floating-ball valves. These full-port valves provide higher flow rates (higher Cv) with minimal in-valve flow interference. Habonim's flanged valves are equipped with the Total HermetiX Integrity Package offering tight shutoff, zero-emission, double body sealing, fire-safe design, and long service life with high durability. Decades of exceptional performance in demanding applications under the most severe working conditions.

78 Series | Stainless Steel



| Size | Port | FTF | Flanged PN40 |
|------|--------|------|--------------------------|
| ½" | DN15 F | ⊙ F1 | 05 F78W-6666ATG/PN40-F1- |
| ½" | DN15 F | ⊙ F4 | 05 F78W-6666ATG/PN40-F4- |
| 1" | DN25 F | ⊙ F1 | 10 F78W-6666ATG/PN40-F1- |
| 1" | DN25 F | ⊙ F4 | 10 F78W-6666ATG/PN40-F4- |
| 1¼" | DN32 F | ⊙ F1 | - |
| 1¼" | DN32 F | ⊙ F4 | 12 F78W-6666ATG/PN40-F4- |
| 1½" | DN40 F | ⊙ F1 | - |
| 1½" | DN40 F | ⊙ F4 | 15 F78W-6666ATG/PN40-F4- |

78 Series | Carbon Steel



| Size | Port | FTF | Flanged PN40 |
|------|--------|------|--------------------------|
| ½" | DN15 F | ⊙ F1 | 05 F78W-4466ATG/PN40-F1- |
| ½" | DN15 F | ⊙ F4 | 05 F78W-4466ATG/PN40-F4- |
| 1" | DN25 F | ⊙ F1 | 10 F78W-4466ATG/PN40-F1- |
| 1" | DN25 F | ⊙ F4 | 10 F78W-4466ATG/PN40-F4- |
| 1¼" | DN32 F | ⊙ F1 | 12 F78W-4466ATG/PN40-F1- |
| 1¼" | DN32 F | ⊙ F4 | 12 F78W-4466ATG/PN40-F4- |
| 1½" | DN40 F | ⊙ F1 | 15 F78W-4466ATG/PN40-F1- |
| 1½" | DN40 F | ⊙ F4 | - |